



CABLE CONNECTORS - SHORT AND STANDARD BUTT SPLICES



CAT. NO	CABLE AWG/MCM	A	C	J	NO. OF CRIMPS	STRIP LENGTH
RCLC 1.5 - 22	16	1.8	3.7	22	4	8 mm
RCLC 2.5 - 22	14	2.4	4	22	4	8 mm
RCLC 4 - 22	12	3.1	4.8	22	4	8 mm
RCLC 6 - 22	10	3.8	5.5	22	4	8 mm
RCLC 10 - 22	6	4.7	7.1	22	4	8 mm
RCDB 16 - 50	6	5.5	8.5	50	4	20 mm
RCLC 16 - 44	6	5.5	7.9	44	4	18 mm
RCDB 25 - 50	4	7	10	50	4	20 mm
RCLC 25 - 48	4	7.1	9.5	48	4	18 mm
RCDB 35 - 50	2	8.2	12.5	50	4	20 mm
RCLC 35 - 48	2	8.2	11.2	48	4	18 mm
RCDB 50 - 56	1/0	10	14.5	56	4	22 mm
RCLC 50 - 48	1/0	9.5	12.8	48	4	18 mm
RCDB 70 - 56	2/0	11.5	16.5	56	4	22 mm
RCLC 70 - 52	2/0	11.2	14.7	52	4	20 mm
RCDB 95 - 70	3/0	13.5	19	70	4	30 mm
RCLC 95 - 54	3/0	13.4	17.4	54	4	22 mm
RCDB 120 - 70	4/0	15.5	21	70	4	30 mm
RCLC 120 - 66	4/0	15.6	20.6	66	4	28 mm
RCDB 150 - 80	300 MCM	17	23.5	80	4	35 mm
RCLC 150 - 66	300 MCM	16.7	22.5	66	4	28 mm
RCDB 185 - 85	350 MCM	19	25.5	85	4	37 mm
RCLC 185 - 66	350 MCM	18.4	24.2	66	4	28 mm
RCDB 240 - 90	500 MCM	21.5	29	90	4	42 mm
RCLC 240 - 91	500 MCM	21.2	28.2	91	4	42 mm
RCDB 300 - 100	600 MCM	24.5	32	100	4	45 mm
RCLC 300 - 91	600 MCM	23.5	31.3	91	4	42 mm
RCDB 400 - 150	750 MCM	27.5	38.5	150	4	70 mm
RCLC 400 - 91	750 MCM	26.8	34.8	91	4	42 mm

FEATURES

- Short & Standard Connectors for regular applications
- Tin Plated to inhibit corrosion
- Material - Electrolytic Copper



CABLE CONNECTORS - BUTT SPLICES CONNECTOR

CAT. NO	CABLE AWG/MCM	A	C	J	MARKING INFORMATION	NO. OF CRIMPS	STRIP LENGTH
RC - 900	8	4.7	7.01	30	8 MH14-RED	3	13 mm
RC - 910	6	5.41	8.51	35	6 MH14-BLU	3	15 mm
RC - 920	4	6.96	10	40	4 UL 100-GREY	4	18 mm
RC - 940	1	9.88	14	50	1-UL 140-PINK	4	24 mm
RC - 950	2/0	11.36	15.5	50	2/0 UL 155-BLK	4	24 mm
RC - 960	2/0	11.95	16.61	55	2/0 UL 166-ORG	4	26 mm
RC - 970	3/0	13.39	18	60	3/0 UL 180-PUR	4	28 mm
RC - 980	4/0	15.06	19.51	65	4/0 UL 194-Y	4	32 mm

FEATURES

- Standard Connectors for regular applications
- Tin Plated to inhibit corrosion
- Material - Electrolytic Copper

