

## CABLE CONNECTORS - BUTT SPLICES (SHORT AND LONG) COLOR CODED




| CAT. NO  | CABLE AWG/MCM | COLOUR CODE | Dimensions in Inches |      |       | NO. OF CRIMPS | STRIP LENGTH |
|----------|---------------|-------------|----------------------|------|-------|---------------|--------------|
|          |               |             | A                    | C    | J     |               |              |
| RC - 111 | 8             | RED         | 4.4                  | 6.9  | 22.9  | 2             | 10 mm        |
| RC - 112 | 6             | BLUE        | 5.2                  | 7.5  | 25.4  | 2             | 12 mm        |
| RC - 113 | 4             | GREY        | 6.4                  | 8.7  | 25.4  | 2             | 12 mm        |
| RC - 114 | 2             | BROWN       | 8                    | 10.7 | 31.8  | 3             | 15 mm        |
| RC - 115 | 2             | GREEN       | 9.1                  | 11.9 | 45.7  | 3             | 21 mm        |
| RC - 116 | 1             | PINK        | 9.9                  | 13.2 | 40.6  | 3             | 18 mm        |
| RC - 117 | 2/0           | BLACK       | 11.2                 | 14.3 | 44.5  | 3             | 20 mm        |
| RC - 118 | 3/0           | ORANGE      | 12.5                 | 15.8 | 44.5  | 3             | 20 mm        |
| RC - 119 | 4/0           | PURPLE      | 13.9                 | 17.5 | 48.3  | 3             | 23 mm        |
| RC - 120 | 250           | YELLOW      | 15.1                 | 19.1 | 50.8  | 3             | 24 mm        |
| RC - 121 | 300           | WHITE       | 16.7                 | 20.7 | 53.3  | 3             | 25 mm        |
| RC - 122 | 350           | RED         | 17.8                 | 22.2 | 53.3  | 3             | 25 mm        |
| RC - 123 | 400           | BLUE        | 19.4                 | 24.1 | 58.4  | 3             | 27 mm        |
| RC - 124 | 500           | BROWN       | 21.2                 | 27   | 63.5  | 4             | 30 mm        |
| RC - 125 | 600           | GREEN       | 23.5                 | 30.2 | 63.5  | 4             | 30 mm        |
| RC - 126 | 750           | BLACK       | 26.2                 | 33.3 | 81.3  | 4             | 40 mm        |
| RC - 127 | 8             | RED         | 4.4                  | 6.9  | 44.5  | 2             | 20 mm        |
| RC - 128 | 6             | BLUE        | 5.2                  | 7.5  | 44.5  | 2             | 20 mm        |
| RC - 129 | 4             | GREY        | 6.4                  | 8.7  | 44.5  | 2             | 20 mm        |
| RC - 130 | 2             | BROWN       | 8                    | 10.7 | 48.3  | 3             | 22 mm        |
| RC - 131 | 1             | GREEN       | 9.1                  | 11.9 | 55.9  | 3             | 26 mm        |
| RC - 132 | 1/0           | PINK        | 9.9                  | 13.2 | 55.9  | 3             | 26 mm        |
| RC - 133 | 2/0           | BLACK       | 11.2                 | 14.3 | 57.2  | 3             | 28 mm        |
| RC - 134 | 3/0           | ORANGE      | 12.5                 | 15.8 | 57.2  | 3             | 28 mm        |
| RC - 135 | 4/0           | PURPLE      | 13.9                 | 17.5 | 69.9  | 3             | 33 mm        |
| RC - 136 | 250           | YELLOW      | 15.1                 | 19.1 | 82.6  | 3             | 40 mm        |
| RC - 137 | 300           | WHITE       | 16.7                 | 20.7 | 89    | 3             | 43 mm        |
| RC - 138 | 350           | RED         | 17.8                 | 22.2 | 95.3  | 3             | 46 mm        |
| RC - 139 | 400           | BLUE        | 19.4                 | 24.1 | 95.3  | 3             | 46 mm        |
| RC - 140 | 500           | BROWN       | 21.2                 | 27   | 108   | 4             | 52 mm        |
| RC - 141 | 600           | GREEN       | 23.5                 | 30.2 | 114.3 | 4             | 55 mm        |
| RC - 142 | 750           | BLACK       | 26.2                 | 33.3 | 120.7 | 4             | 57 mm        |

### FEATURES

- Short & Long Connectors for Heavy Duty applications
- Tin Plated to inhibit corrosion
- Material - Electrolytic Copper



Butt Splice



Diagram

## CABLE CONNECTORS - FLARED MOUTH INLINE CONNECTOR

| PART NO COPPER FINISH | PART NO TIN FINISH | WIRE RANGE | Dimensions in Inches |        |        | NO. OF CRIMPS | STRIP LENGTH |
|-----------------------|--------------------|------------|----------------------|--------|--------|---------------|--------------|
|                       |                    |            | A                    | C      | J      |               |              |
| RC - 333              | RC 333 T           | 8          | 4.7244               | 6.35   | 27.94  | 4             | 12 mm        |
| RC - 334              | RC 334 T           | 6          | 5.5928               | 7.925  | 29.21  | 4             | 14 mm        |
| RC - 335              | RC 335 T           | 4          | 7.1374               | 9.042  | 30.988 | 4             | 14 mm        |
| RC - 336              | RC 336 T           | 2          | 8.4328               | 10.668 | 34.036 | 2             | 16 mm        |
| RC - 337              | RC 337 T           | 1          | 8.9408               | 11.176 | 34.036 | 2             | 16 mm        |
| RC - 338              | RC 338 T           | 1/0        | 10.1854              | 12.649 | 39.624 | 2             | 18 mm        |
| RC - 339              | RC 339 T           | 2/0        | 11.5824              | 14.224 | 45.974 | 2             | 20 mm        |
| RC - 340              | RC 340 T           | 3/0        | 12.9286              | 15.621 | 48.26  | 2             | 22 mm        |
| RC - 341              | RC 341 T           | 4/0        | 14.9352              | 17.628 | 62.484 | 2             | 26 mm        |

### FEATURES

- Bell Mouth Connectors (Flared) for easy entry of conductor
- Tin Plated to inhibit corrosion
- Material - Electrolytic Copper



Flared Mouth Connector